

6CX-530 Series


Configuration	4-stroke, vertical, water cooled diesel engine		
Maximum output at crankshaft	* 390 kW@2900 rpm	[530 mhp@2900 rpm]	
Continuous rating output at crankshaft	355 kW@2809 rpm	[482 mhp@2809 rpm]	
Displacement	7.413 ltr	[452 cu in]	
Bore x stroke	110 mm x 130 mm	[4.33 in x 5.12 in]	
Cylinders	6 in-line		
Combustion system	Direct injection		
Aspiration	Dry turbocharger with water-cooled jacket, charge-air cooler		
Starting system	Electric starting 12V [24V = optional]		
Alternator	12V - 120A [24V - 60A = optional]		
Cooling system	Fresh water cooling by centrifugal fresh water pump and rubber impeller seawater pump		
Lubrication system	Enclosed, forced lubricating system		
Direction of rotation [crankshaft]	Counter clockwise viewed from flywheel side		
Dry weight without gear	837 kg	[1845 lb]	
Environmental	EU: RCD		
	US: EPA	Tier2	EMC
Engine mounting	Rubber type flexible mounting		

NOTE: Fuel condition: Density at 15°C = 0.84 g/cm³


* Fuel temperature 40°C at the inlet of the fuel injection pump [ISO 8665: 2006]

DIMENSIONS [UNIT: MM]




Front view with gearbox KMH70A



Right side view with gearbox KMH70A




PERFORMANCE CURVES



MARINE GEARS SPECIFICATIONS

Model	KM70A			
Type	Hydraulic multi-disc clutch			
Dry Weight	77 kg			
Reduction Ratio [Ahead]	2.56	2.07	1.57	1.23
Propeller speed [@2900 rpm]	1133	1401	1847	2358
Dry weight engine and gear/drive	914 kg [2015 lb]			

NMEA2000 CONTROL SYSTEM



ACCESSORIES

Optional accessories

- Flexible mounts
- NMEA2000 Control heads
- NMEA2000 Display and Gauges
- 24V System

NOTE: All data subject to change without notice. Text and illustrations are not binding.